

# RA-20

## Remote Annunciator Module

Together with GCU-20 Module or other ECU with Annunciator output

### Features

- Works Up to 1500 Meters from The Host Module Using 18 AWG Cable (@12/24VDC)
- Universal LED Graphic Interface, Displays Generator Status and Failures
- Modular Design, Quick Installation
- Circuits are Finger Safe with UL94-V0 Epoxy Protection
- Simplify All Wiring with Pluggable Terminal Block
- Easy Assembly & Maintenance with No Chance of Wiring Mistakes



### Icon Reference Table

Icon	Description	Icon	Description
	<ul style="list-style-type: none"><li>● Low Oil Pressure Alarm</li><li>● Auxiliary Alarm (Flashing)</li></ul>		<ul style="list-style-type: none"><li>● Wrong speed Alarm</li><li>● No Speed Signal Alarm (Flashing)</li></ul>
	<ul style="list-style-type: none"><li>● High Water Temperature Alarm</li></ul>		<ul style="list-style-type: none"><li>● Engine Running Indicator</li><li>● Engine IDLE Indicator (Flashing)</li></ul>
	<ul style="list-style-type: none"><li>● Over Crank Alarm</li></ul>		<ul style="list-style-type: none"><li>● Common Alarm Indicator</li></ul>

### Specifications

Rated Input Voltage	9 to 36 VDC
Working Distance from Host ECU	1500 Meters
Standard Cable	18 AWG

Terminal Block Capacity	300 VAC / 15A
Power Consumption	Under 1 watt

### Environment

Operating Temperature	-20~70 °C
Storage Temperature	-35~85 °C
Relative Humidity	Maximum 90%

### Physical Specification

Dimensions	88.0 (L) x 88.0 (W) x 37.5 (H) mm
Weight	143 g $\pm$ 2%

### Mechanical Specifications (Unit : mm[inch] )

### Installing Panel

