

# DSE860/865

## SINGLE-SET COMMUNICATIONS DEVICES

The DSE860 and DSE865 are communications devices that allow you to monitor single or multiple generating sets over a LAN (network) or WAN (internet) connection. The devices include software that is used to assign a TCP/IP address to a COM Port on a PC.

This COM port is then selected by the user in the standard PC software of the DSE module being used. Once this COM port has been selected then the user can communicate directly with the control module from their PC.

If the device needs to be seen over the internet the assigned IP address has to be configured to be visible to the outside world. Once this has been done the module can be communicated with from any remote location that has internet connectivity. The devices have been designed to work with the DSE55xx, DSE73xx, DSE75xx DSE86xx and DSE87xx control modules.

The devices also include LED indicators that show the operation and connection status at all times. Different light patterns indicate a range of status conditions.

### KEY FEATURES

- Can be used over an internal network and the internet
- LED status indicators on the devices aid fault finding
- TCP/IP software is extremely easy to use
- Devices automatically reconnect in the event of loss of communication
- Fully customer configurable settings
- DIN rail mounting

### KEY BENEFITS

- Works with the DSE55xx, DSE73xx, DSE75xx DSE86xx and DSE87xx control modules
- Generic connectors for simple plug-in operation
- DIN rail mounting allows devices to be installed securely within a panel
- Allows users (one user at any one time) from different locations to view generator status



### SPECIFICATION

#### DC SUPPLY

8 V to 35 V DC Continuous

#### ETHERNET CONNECTION

10Base-T or 100Base-TX (IEEE 802.3). RJ45 connector

#### COVER MATERIAL

Grey/Black plastic, LEXAN 940, self extinguishing acc. To UL94-V0

#### MOUNTING OPTION

DIN rail (EN50022)

#### DIMENSIONS

86 mm x 35 mm x 57 mm  
3.4" x 1.4" x 2.2"

### ENVIRONMENTAL TESTING STANDARDS

#### ELECTRO-MAGNETIC COMPATIBILITY

BS EN 61000-6-2  
EMC Generic Immunity Standard for the Industrial Environment  
BS EN 61000-6-4  
EMC Generic Emission Standard for the Industrial Environment

#### ELECTRICAL SAFETY

BS EN 60950  
Safety of Information Technology Equipment, including Electrical Business Equipment

#### TEMPERATURE

BS EN 60068-2-1  
Ab/Ae Cold Test -30 °C  
BS EN 60068-2-2  
Bb/Be Dry Heat +70 °C

#### VIBRATION

BS EN 60068-2-6  
Ten sweeps in each of three major axes  
5 Hz to 8 Hz @ +/-7.5 mm,  
8 Hz to 500 Hz @ 2 gn

#### HUMIDITY

BS EN 60068-2-30  
Db Damp Heat Cyclic 20/55 °C @ 95% RH 48 Hours  
BS EN 60068-2-78  
Cab Damp Heat Static 40 °C @ 93% RH 48 Hours

#### SHOCK

BS EN 60068-2-27  
Three shocks in each of three major axes  
15 gn in 11 ms

### RELATED MATERIALS

TITLE	PART NO'S	TITLE	PART NO'S
DSE860 865 Manual	057-099	DSE 8610 Date Sheet	055-083
DSE5510 Data Sheet	055-039	DSE 8660 Date Sheet	055-086
DSE 5520 Date Sheet	055-040	DSE 8700 Date Sheet	055-090
DSE 5560 Date Sheet	055-041	DSE7520 Data Sheet	055-066
DSE7310/20 Data Sheet	055-051	DSE7560 Data Sheet	055-067
DSE7510 Data Sheet	055-065		



### DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH  
**TELEPHONE** +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303  
**EMAIL** sales@deepseapl.com **WEBSITE** www.deepseapl.com

### DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA  
**TELEPHONE** +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708  
**EMAIL** sales@deepseausa.com **WEBSITE** www.deepseausa.com